wall primer application notes



Lullaby Paints WALL PRIMER

Description	Lullaby Paints Wall Primer
Storage	Protect from frost/freezing
Where to Use	Interior walls and ceilings - for priming and sealing dry, bare plaster and plasterboard prior to painting
Preparation	 Ensure the woodwork is sound, smooth, dry and free of dust, dirt and grease. Knots should be treated with two liberal coats of ECOS white knotting* Fillers should be sealed with Filler Sealer Bare hardwoods - call us at 864.595.3840 for assistance
Application	 Stir gently and thoroughly before use Ensure that the plaster is dry and dust free, non greasy and clean Avoid applying below 41°F (5°C) and above 68°F (20°C) Apply by brush or roller Spread so as to give an even, thin coverage Allow to dry thoroughly before painting Clean equipment with water, as soon as you have finished painting
Drying Time	 Is highly dependent on conditions of use, but normal drying is in the range of 1 to 4 hours (depending on the porosity of the plaster, local ventilation and temperature)
Coverage	 Varies with porosity, but on hard non-porous surfaces estimate: 260 sq. ft. per quart (single coat) 430 sq. ft. per gallon (single coat)
Health and Safety	 Avoid contact with skin and eyes. Wash off splashes with water. Do not ingest WARNING: Older buildings may contain lead-based paint, which requires professional remediation if it is disturbed. If in doubt, consult with a professional from a Lead-Safe Certified Firm.



More Tips:

Getting the Most Out of Your Pouch

Twist and squeeze pouch for full use. In addition, the pouch can be cut open using scissors. Squeeze out air before resealing

Discarding Paint Pouches

Let dry in an air cooled place and discard in accordance with local ordinance

Help us to provide a healthy, safe environment for moms and babies

* Where to Find ECOS Paints http://www.ecospaints.net

